

360°


Hardwired Detection System

OPTEX, the leader in the world market share of the security sensors and systems for intrusion detection with over 39 years experience, we has been trusted and received high marks of appreciation for the durability and reliability of quality detection technology by worldwide customer.

To increase the effectiveness of security system, OPTEX recommends not only securing the inside of the building but also adding surveillance to the perimeter area and boundary of the property. OPTEX has developed a system of enhanced outdoor surveillance that is capable of forestalling unauthorized entry into a building.


By integrating outdoor and indoor surveillance, this system creates a defense line incorporating three warning levels targeting the perimeter of the property, the boundary of the building, and the indoor area. As a result, we can greatly strengthen and improve crime prevention.

COMMERCIAL/INDUSTRIAL



SOLUTIONS

INTRUDER ALARM



SAFETY ALERT




PTZ camera control and DVR recording




DRIVEWAY ALERT



LIGHTING TRIGGER



WARNING ALERT



SOLUTION BY PIDS - Increasing Security costs

1. Problem: Increasing Security costs


2. Solution: Case Study example

	ltem	Expense	
Before	Necessary security guard power (Day shift + 24/7 shift)	50 guards	
	Security guard cost (\$ 20,000/guard/month)	₿ 1,000,000	
	Security guard cost (year)	в 12,000,000	

	Item	PIDS	PIDS added to existing CCTV	
After	Necessary security guard power	40 guards (20 % reduction)	35 guards (30 % reduction)	
	Security guard cost (\$ 20,000/guard/month)	₿ 800,000	в 700,000	
	Security guard cost (year)	₿ 9,600,000	₿ 8,400,000	
Compare	Difference of Security guard cost (year)	- B 2,400,000	- B 3,600,000	

Cost simulation

- PIDS added to existing CCTV case -



Item	Before/After	Security No.	year 1	year 2	year 3	year 4	year 5		
Annual cost	Before	50	B 12,000,000	B 12,000,000	B 12,000,000	B 12,000,000	B 12,000,000		
	After	35	₿ 8,800,000	₿ 8,400,000	B 8,400,000	B 8,400,000	₿ 8,400,000		
Accumulated cost	Before	50	B 12,000,000	\$ 24,000,000	B 36,000,000	B 48,000,000	₿ 60,000,000		
	After	35	₿ 8,800,000	B 17,200,000	B 25,600,000	B 34,000,000	B 42,400,000		
Accumulated cost difference			₿ 3,200,000	₿ 6,800,000	B 10,400,000	₿ 14,000,000	B 17,600,000		

 $[\]ensuremath{^{*}}$ All cost information is just an example and the actual cost varies according to site.

Solution by PIDS







OPTEX Hardwired Sensor



AX-70TN/130TN/200TN/100TF/200TF

SHORT RANGE / HARD-WIRED

AX-70TN:20m , AX-130TN:40m, AX-200TN:60m AX-100TF: 30m, AX-200TF:60m

[FEATURES]

- Selectable 4ch beam frequencies (AX-TF only)
- IP65 protection



SL-200QDP/350QDP/650QDP SL-200QDM/350QDM/650QDM

ADVANCED / HARD-WIRED

SL-200QDP/200QDM:60m SL-350QDP/350QDM:100m SL-650QDP/650QDM:200m

- [FEATURES] - Quad high power beams
- Double modulation
- Sniper viewfinder
- IP65 protection

(SL-QDM only)

A.T.P.C. to optimize the beam power

I.A.S.C. to optimize the transmitter and the receiver



FTN-ST

COMPACT OUTDOOR DETECTOR

: 2PIRs standard model FTN-ST

[FEATURES]

- Intelligent AND detection logic
- Built in bracket (190° horizontal)
- 5m/2m switchable lens
- SMDA Logic



SL-200QN/350QN/650QN

MIDDLE & LONG RANGE / HARD-WIRED

SL-200QN:60m SL-350QN:100m SL-650QN:200m

[FEATURES]


- Quad high power beams
- Sniper viewfinder
- IP65 protection

BX-80N

OUTDOOR DETECTOR FOR BUILDING PERIMETER

[FEATURES]

- Multiple detection pattern technology
- Limited detection range function
- Patented double conductive shielding
- Audible alarm function
- Advanced temperature compensation





VXI-ST

MULTI DIMENSIONAL OUTDOOR DETECTOR

VXI-ST : 12m/90° battery operated model

[FEATURES]

 SMDA logic for temperature compensation

- Easy masking for over spill prevention





HX-40

HIGH MOUNT OUTDOOR DETECTOR

: 12m/85° standard model

[FEATURES]

- Mounting height: 2.5 to 3m - Intelligent AND detection logic
- Form C alarm output and
- tamper output



HX-80N

LONG AND NARROW RANGE HIGH MOUNT OUTDOOR DETECTOR

HX-80N : 24m/narrow standard model

[FEATURES]

- Mounting height: 2.5 to 3m
- Intelligent AND detection logic





CX-702 (21m/45m)

LONG RANGE PIR DETECTOR WITH SELECTABLE **DETECTION PATTERN**



SIP-Series

OUTDOOR DETECTOR / HARD-WIRED

[FEATURES]

- Mounting height up to 4m - Reduction of false alarm
- Protection from vandalism



OPTEX CO., LTD. (JAPAN) URL: http://www.optex.co.jp/e/sec

OPTEX INC. / AMERICAS HQ (U.S.)

URL: www.optexamerica.com

OPTEX (EUROPE) LTD. / EMEA HQ (U.K.)

URL: www.optex-europe.com

OPTEX DO BRAZIL LTDA. (Brazil)

URL: www.optex.eu

OPTEX TECHNOLOGIES B.V. (The Netherlands)

URL: www.optex.eu

OPTEX SECURITY SAS (France)

URL: www.optex-security.com

OPTEX SECURITY Sp.z o.o. (Poland)

URL: www.optex.com.pl

OPTEX PINNACLE INDIA, PVT., LTD. (India)

URL: www.optex.net/in/en/sec

OPTEX KOREA CO., LTD. (Korea)

URL: www.optexkorea.com

OPTEX (DONGGUAN) CO., LTD. SHANGHAI OFFICE (China)

URL: www.optexchiana.com

OPTEX (THAILAND) CO., LTD. (Thailand)

URL: www.optex.co.th